AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

- 1. (Canceled)
- 2. (Currently Amended) A device for use in association with a multimedia system for capturing and reproducing at least audio signals, the device being
 - A) associated with plurality of microphones; and
 - B) configured to selectively operate to perform one of:
- ii) synthetic aperture microphone processing on the audio signals captured by at least some of the associated microphones for producing at least one synthetic aperture microphone audio signal.
- 3. (Currently amended) The device of claim 2, wherein the adaptive acoustic stereo echocanceling <u>operations</u> and synthetic <u>aperture</u> microphone processing capabilities are combined in a single packaging.
- 4. (Canceled)
- 5. (Previously Presented) The device of claim 2, wherein the synthetic aperture microphone processing adjusts a position of a spatial region corresponding to the area of maximum sensitivity of the synthetic aperture microphone function.
- 6. (Currently Amended) The device of claim 2, wherein saidthe synthetic aperture microphone processing comprises performing at least one of a delay or frequency dispersion operation on the audio signal.
- 7. (Currently Amended) The device of claim 2, <u>further</u>-comprising A/V elements <u>configured</u> to receive, <u>transmit</u>, <u>encode</u>, <u>and decode for</u> audio and video signals. <u>reception and transmission</u>; and audio and video signal encoding and decoding.

- 8-56. (Canceled)
- 57. (Currently Amended) The device of claim [[54]]2, the device further comprising: a network-port configured to for coupling said couple the device to a workstation.
- 58-62. (Canceled)
- 63. (Currently Amended) The device of claim 2, wherein each of the stereo echo-canceling audio signals and the synthetic aperture microphone audio signals are produced from the same microphone audio signals.
- 64-66. (Canceled)
- 67. (New) The device of claim 2, wherein the acoustic stereo echo-canceling operations and the synthetic aperture microphone processing are performed in a single processor.
- 68. (New) A method of capturing and reproducing at least audio signals, the method comprising:
 - A) receiving audio signals from a plurality of microphones, and
 - B) selectively operating to perform at least one of:
- i) adaptive acoustic stereo echo-canceling operations on the audio signals received from at least some of the microphones to produce at least one stereo echo-canceling audio signal; and
- ii) synthetic aperture microphone processing on the audio signals received from at least some of the microphones to produce at least one synthetic aperture microphone audio signal.
- 69. (New) The method of claim 68, wherein the acoustic stereo echo-canceling operations and the synthetic aperture microphone processing are performed in a single processor.
- 70. (New) The method of claim 68, wherein the stereo echo-canceling audio signals and the synthetic aperture microphone audio signals are produced from the same audio signals.
- 71. (New) The method of claim 68, wherein the synthetic aperture microphone processing adjusts a position of a spatial region corresponding to the area of maximum sensitivity of the synthetic aperture microphone function.
- 72. (New) A multimedia collaboration system, the system comprising:

a plurality of audio signals received from a plurality of microphones; wherein the system selectively operates to perform at least one of:

- i) adaptive acoustic stereo echo-canceling operations on the audio signals received from at least some of the plurality of microphones to produce at least one stereo echo-canceling audio signal; and
- ii) synthetic aperture microphone processing on the audio signals received from at least some of the plurality of microphones to produce at least one synthetic aperture microphone audio signal.
- 73. (New) The system of claim 72, wherein the adaptive acoustic stereo echo-canceling operations and synthetic aperture microphone processing are combined in a single packaging.
- 74. (New) The system of claim 72, wherein the acoustic stereo echo-canceling operations and the synthetic aperture microphone processing are performed in a single processor.
- 75. (New) The system of claim 72, wherein the stereo echo-canceling audio signals and the synthetic aperture microphone audio signals are produced from the same audio signals.
- 76. (New) The system of claim 72, wherein the synthetic aperture microphone processing adjusts a position of a spatial region corresponding to the area of maximum sensitivity of the synthetic aperture microphone function.
- 77. (New) The system of claim 72, wherein the synthetic aperture microphone processing includes performing at least one of a delay or frequency dispersion operation on the audio signal.
- 78. (New) The system of claim 72, including A/V elements configured to receive, transmit, encode, and decode audio and video signals.
- 79. (New) The system of claim 72, wherein the system is coupled to a workstation.